University of Calicut

(Purchase Division)

63696/PURCHASE-ASST-A1/2013/CU

Dated 07.10.2017

QUOTATION NOTICE

Sealed quotations are invited by the Registrar, University of Calicut for the supply of one DSLR Camera to the Psychology Department as per the specifications given in the schedule below. The rates quoted should include taxes and all other charges including charges for delivery of the articles at the place mentioned in the schedule below.

Quotation Number	63696/PURCHASE-ASST-A1/2013/CU dated07.10.2017	
Last date and Time for the receipt of Quotation	23.10.2017 4 P.M.	
Date and Time for opening the Quotation	24.10.2017 11 A.M.	
Date up to which rates are to be firm	90 days from acceptance of quotation	
Designation and address of officer to whom the quotation is to be addressed	Deputy Registrar, Purchase Division, University of Calicut, Thenhipalam, University P.O. Malappuram 673 635	
Superscription	Quotation for purchase of camera to Deptartment of Psychology	
Address for Delivery	The Head, Department of Psychology, University of Calicut, Thenhipalam, University P.O. Malappuram 673 635	

The necessary superscription, due date for the receipt of quotations, the date up to which the rates will have to remain firm for acceptance and the name, address of officer to whom the quotation and place to be sent are noted above.

Any quotation received after the time fixed on the due date is liable to be rejected. On acceptance of quotation the articles should be delivered within a period of 7 days.

SCHEDULE OF ITEMS

DSLR Camera:

DSLR Camera.		
Туре		
Туре	Digital, single-lens reflex, AF/AE camera with built-in flash	
Recording media	SD memory card, SDHC memory card, SDXC memory card	
	Compatible with UHS-I	
	8 GB Memory card should be provided with the camera	
Compatible lenses	EF lenses	
	2 lenses viz 18-55 mm & 55-250 mm should be provided along with	
	the camera	
Lens mount	EF mount	
Image Sensor		
Туре	CMOS sensor	
Effective pixels	18 megapixels	
Aspect ratio	3:2	
Dust delete feature	Auto, Manual, Dust Delete Data appending	

	JPEG, RAW	
lmage type	RAW+JPEG Large simultaneous recording possible	
Image Processing		
During Shooting		
Picture style	Auto, Standard, Portrait, Landscape, Neutral, Faithful, Monochrome User Def. 1 - 3	
White balance	Auto, Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescenlight, Flash), Custom White balance correction and white balance bracketing features should be provided	
Noise reduction	Applicable to long exposures and high ISO speed shots	
Auto image brightness correction		
	Peripheral illumination correction, Chromatic aberration correction	
Viewfinder		
Туре	Eye-level pentamirror	
Coverage	Vertical / Horizontal approx. 95% (with Eye point approx. 19mm)	
Magnification	Approx. 0.85x (-1m-1 with 50mm lens at infinity)	
Eyepoint	Approx. 19mm (from eyepiece lens center at -1m-1)	
Built-in dioptric		
Focusing screen	Fixed, Precision Matte	
Autofocus		
Туре	TTL secondary image-registration, phase detection	
AF points	Nine cross-type AF points (Cross-type AF sensitive to f/2.8 with center AF point)	
ocusina brightness	EV -0.5 - 18 (center AF point, at 23°C / 73°F, ISO 100)	
AF operation	One-Shot AF, Al Servo AF, Al Focus AF	
AF-assist beam	Small series of flashes fired by built-in flash	
Exposure Control	The second of med by bent-in hasir	
	EV 1 - 20 (at 23°C / 73°F with EF50mm f/1.6 II lens, ISO 100)	
Exposure control	Program AE (Scene Intelligent Auto, Flash Off, Creative Auto, Portrait, Landscape, Close-up, Sports, Special scene (Night Portrait, Handheld Night Scene, HDR Backlight Control), Program), Shutter-priority AE, Aperture-priority AE, Manual exposure	
	ISO 100 - ISO 6400 set automatically, Handheld Night Scene: ISO 100 - ISO 12800 set automatically	
SO speed	ISO 100 - ISO 1280	
Recommended xposure index)	set manually (whole stop increments), ISC 100 - ISO 6400 se	

·			
	Creative zone modes:	automatically, maximum ISO speed settable for ISO Auto, or ISO expansion to	
·	· · · · · · · · · · · · · · · · · · ·	"H" (equivalent to ISO 25600)	
	Manual:	±5 stops in 1/3- or 1/2-stop increments	
Exposure	AEB:	±2 stops in 1/3- or 1/2-stop increments (Can be combined with manual exposure compensation)	
AE lock	Auto:	Applied in One-Shot AF with evaluative metering when focus is achieved	
	Manual:	With AE lock button	
Shutter	1		
Гуре	Electronically-controlled, focal-plane shutter		
Shutter speeds	1/4000sec. to 30secs. (Total shutter speed range. A shooting mode.), Bulb, X-sync at 1/200sec.	Available range varies by	
Flash			
,	Retractable, auto pop-up flash		
	Guide No.:	Approx. 13/43 (ISC 100, in meters/feet)	
Built-in flash	Flash coverage:	Approx. 17mm len angle of view	
J.a	Recycling time approx. 3secs.		
	Wireless master function should be provided		
External flash	Flash functions settable with the camera		
Flash metering	E-TTL II autoflash		
Flash exposur compensation	e ±2 stops in 1/3- or 1/2-stop increments		
Drive System			
Drive mode	Single shooting, continuous shooting, self-timer delay and 10-secs. delay with continuous shooting	with 10-secs. or 2-secs.	
Continuous shootin speed	Max. approx. 5.0 shots/sec.		
	JPEG Large / Fine:	22 (30) shots	
Max. burst (Approx.):	RAW: RAW + JPEG Large / Fine:	6 (6) shots 3 (3) shots	
Live View Shootings			
Aspect ratio settings	3:2, 4:3, 16:9, 1:1		
Focusing	Hybrid CMOS AF System, Phase-difference detection Manual focusing (approx. 5x / 10x magnification po		
	Focusing brightness range: EV 1 - 18 (at 23°C / 73	°F, ISO 100)	

Continuous (pre) AF	Should be Provided	4	
Touch shutter	Should be Provided		
	Real-time metering with image sensor		
N 4 - 4	Evaluative metering (315 zones). Partial meter	oring (0.00/ 5.1.)	
Metering modes	View screen), Spot metering (approx. 2.8% of	Live View serses O	
	weighted average metering	Live view screen), Cente	
Metering brightnes			
range	EV 0 - 20 (at 23°C / 73°F with EF50mm f/1.4 US	SM lens, ISO 100)	
Creative filters	Grainy B/W, Soft focus, Fish-eye effect, Art bold effect, Water pai		
	effect, Toy camera effect, Miniature effect		
Movie Shooting			
Recording format	MOV		
Movie	MPEG-4 AVC / H.264 Variable (average) bit rate		
Audio	Linear PCM		
Recording size and	1920 x 1080 (Full HD):	30p / 25p / 24p	
frame rate	1280 x 720 (HD):	60p / 50p	
	640 x 480 (SD):	30p / 25p	
	1920 x 1080 (30p / 25p / 24p):	Approx. 330 MB/min	
File size	1280 x 720 (60p / 50p):	Approx. 330 MB/min	
	640 x 480 (30p / 25p):	Approx. 82.5 MB/mir	
ocusing	Hybrid CMOS AF System	7 PP-031 0210 1112/1111	
- Journal of the second of the	Manual focusing (approx. 5x / 10x magnification	possible)	
Metering modes	Center-weighted average and evaluative metering with the image sensor		
	Automatically set by the focusing mode		
/ideo snapshots	Settable to 2 secs. / 4 secs. / 8 secs.		
The second second	Built-in stereo microphone		
Sound recording	External stereo microphone terminal provided		
	Sound recording level adjustable, wind filter provided, attenuator provided		
ype	TFT color liquid-crystal monitor		
ype	TFT color liquid-crystal monitor Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million		
ype Monitor size and dots			
ype Monitor size and dots angle adjustment	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million		
ype Monitor size and dots angle adjustment brightness adjustment	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels)		
ype Monitor size and dots Ingle adjustment Irightness adjustment Ouch screen	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels)		
ype Monitor size and dots angle adjustment brightness adjustment ouch screen echnology	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels)		
	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing		
ype Monitor size and dots angle adjustment rightness adjustment ouch screen echnology eature guide liayback	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing	on dots	
Monitor size and dots Ingle adjustment Irightness adjustment Iouch screen Iechnology Ieature guide Iliayback Inage display formats	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable	on dots	
ype Monitor size and dots Ingle adjustment Irightness adjustment Ouch screen Inchnology eature guide Ilayback Inage display formats	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display	on dots	
Monitor size and dots Ingle adjustment Irightness adjustment Iouch screen Inchnology I eature guide I layback I mage display formats I oom magnification	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display histogram), 4-image index, 9-image index	on dots	
Monitor size and dots Ingle adjustment Orightness adjustment Ouch screen echnology eature guide Playback mage display formats Coom magnification lighlight alert mage browsing	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display histogram), 4-image index, 9-image index Approx. 1.5x - 10x	on dots v (Basic info, shooting info,	
Monitor size and dots Ingle adjustment Irightness adjustment Iouch screen Inchnology Inc	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display histogram), 4-image index, 9-image index Approx. 1.5x - 10x Overexposed highlights blink Single image, jump by 10 or 100 images, by shapping image, by stills, by rating	on dots v (Basic info, shooting info,	
Monitor size and dots Ingle adjustment Brightness adjustment Ouch screen echnology eature guide Iliayback Inage display formats oom magnification Ilighlight alert Inage browsing nethods	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display histogram), 4-image index, 9-image index Approx. 1.5x - 10x Overexposed highlights blink Single image, jump by 10 or 100 images, by sh	on dots v (Basic info, shooting info,	
Monitor size and dots Angle adjustment Brightness adjustment Ouch screen echnology eature guide Playback mage display formats oom magnification lighlight alert	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display histogram), 4-image index, 9-image index Approx. 1.5x - 10x Overexposed highlights blink Single image, jump by 10 or 100 images, by shadowies, by stills, by rating Possible Should be provided	on dots v (Basic info, shooting info, nooting date, by folder, by	
Monitor size and dots Ingle adjustment Orightness adjustment Ouch screen echnology eature guide Diayback mage display formats oom magnification lighlight alert mage browsing methods mage rotate	Wide, 7.7cm (3.0-in.) (3:2) with approx. 1.04 million Possible Manual (7 levels) Capacitive sensing Displayable Single-image display, Single-image + info display histogram), 4-image index, 9-image index Approx. 1.5x - 10x Overexposed highlights blink Single image, jump by 10 or 100 images, by shadowies, by stills, by rating Possible	on dots v (Basic info, shooting info, nooting date, by folder, by	

Slide show	All images, by date, by folder, by movies, by Stills, by tating Five transition effects selectable	
Background music	Selectable for slide shows and movie playback	
Post-Processing of Images		
Creative filters	Grainy B/W, Soft focus, Fish-eye effect, Art bold effect, Water painting effect, Toy camera effect, Miniature effect	
Resize	Should be possible	
Direct Printing		
Printable images	JPEG and RAW images	
Print ordering	DPOF Version 1.1 compatible	
Interface		
Audio / video OUT / Digital terminal	Analog video (compatible with NTSC / PAL) / stereo audio output Personal computer communication and direct printing (Hi-Speed USB equivalent), GPS Receiver GP-E2 connection	
HDMI mini OUT terminal	Type C (auto switching of resolution), CEC-compatible	
External microphone IN terminal	3.5mm diameter stereo mini-jack	
Remote control terminal	For Remote Switch RS-60E3	
Wireless remote control	Remote Controller RC-6	
Eye-Fi card	Compatible	
Power		
Battery	Battery Pack	
Operation Environment		
Working temperature range	0°C - 40°C / 32°F - 104°F	
Working humidity	85% or less	
Carry Case	Should be provided	
Warranty	1 Year.	

General Conditions:-

- 1. Acceptance of the quotation constitutes a concluded contract.
- 2. Withdrawal from the quotation after it is accepted or failure to supply within a specified time or according to specifications will entail cancelation of the order and purchases being made at the offerers expenses from elsewhere, any loss incurred thereby being payable by the defaulting party. In such an event the Government reserves also the right to remove the defaulter's name from the list of Government suppliers permanently or for a specified number of years.
- 3. Samples, duly listed, should be forwarded if called for under separate cover and the unapproved samples got back as early as possible by the offerers at their own expenses and the Government will in no case be liable for any expenses on account of the value of the samples or their transport charges, etc. In case, the samples are sent by railway; the railway receipt should be sent separately, and not along with the quotation since the quotation will be opened only on the appointed day and demurrage will have to be paid if the railway parcels are not cleared in time. Quotations for the supply of materials are liable to be rejected unless samples, if called for of the materials tendered for are forwarded. The approved

samples may or may not be returned at the discretion of the undersigned. Samples sent by V.P. Post or "freight to pay" will not be accepted.

- 4. No representation for enhancement of price once accepted will be considered during the currency of the contract.
- 5. Any attempt on the part of tenderers or their agents to influence the Officers concerned in their favour by personal canvassing will disqualify the tenderers.
- 6. If any license or permit is required, tenderers must specify in their quotation and also state the authority to whom application is to be made.
- 7. The quotation may be for the entire or part supplies. But the tenderers should be prepared to carry out such portion of the supplies included in their quotation as may be allotted to them.
- 8. (a) In cases where a successful tenderer, after having made partial supplies fails to fulfill the contracts in full, all or any of the materials not supplied may, at the discretion of the Purchasing Officer be purchased by means of another tender/quotation or by negotiation or from the next higher tenderer who had offered to supply already and the loss, if any, caused to the Government shall thereby together with such sums as may be fixed by the Government towards damages be recovered from the defaulting tenderer. (b) Even in cases where no alternate purchases are arranged for the materials not supplied, the proportionate portion of the security deposit based on the cost of the materials not supplied at the rate shown in the tender of the defaulter shall be forfeited and balance alone shall be refunded. (c) Any sum of money due and payable to the contractor (including Security Deposit returnable to him) under this contract may be appropriated by the Purchasing Officer or Government or any other person authorized by Government and set-off against any claim of the Purchasing Officer or Government for the payment of a sum of money arising out of or under any other contract made by the contractor with the Purchasing Officer or Government or any other person authorized by Government.
- 9. The prices quoted should be inclusive of all taxes, duties, cess, etc., which are or may become payable by the contractor under existing or future laws or rules of the country of origin/supply or delivery during the course of execution of the contract. The bidder should have valid GST registration and should furnish the GST number in the quotation.
- 10. The tenderers shall quote also the percentage of rebate (discount) offered by them in case the payment is made promptly within fifteen days/within one month of taking delivery of stores.
- 11. Any sum of money due and payable to the successful tenderer or contractor from Government shall be adjusted against any sum of money due to Government from him under any other contracts.
- 12. The final acceptance of the tenders rests entirely with the University who do not bind themselves to accept the lowest or any tender. But the tenderers on their part should be prepared to carry out such portion of the supplies included in their tenders as may be allotted to them.
- 13. Special conditions, if any, printed on the quotation sheets of the tenderer or attached with the tender will not be applicable to the contract unless they are expressly accepted in writing by the purchases.

Calicut University

(replace

Shajee K